



WALINGA[®]
3510 AGRI-VAC^{INC.}



3510 Agri-Vac

The 3510 AGRI-VAC, equipped with a WALINGA #510 blower, can move up to 900 bu/hr (23 tonnes/hr). Weighing less than 1400 lbs. (635 kg), it can be used in the tightest corners to perform transfer, cleanup or loading operations. The 3510 moves grain on a cushion of air which minimizes grain or seed damage. This is important to maintain grain and seed quality. The 3510 gas/electric model is mounted on a formed steel, three wheeled cart, with fork-lift pockets making it very simple to move into the smallest corner of your storage area. Available in 30 hp gas, 10/15/20 hp electric, or with a 3 point hitch, it is the ideal unit for someone who needs a versatile and portable grain handling unit.

CLEAN UP

- Portable
- Efficient
- Versatile



SPECIFICATIONS:

	3510G (gasoline)	3510E (electric)	3510 3PH (PTO)
Weight	1373 lbs. (623 kg)	1373 lbs. (623 kg)	900 lbs (410 kg)
Height	73 inch (185 cm)	73 inch (185 cm)	60 inch (152 cm)
Width	34 inch (86 cm)	34 inch (86 cm)	47 inch (119 cm)
Length	78 inch (198 cm)	78 inch (198 cm)	78 inch (198 cm)
Wheels	3 pneumatic (1 on swivel)	3 pneumatic (1 on swivel)	mounted on legs
Blower	#510 Walinga blower	#510 Walinga blower	#510 Walinga blower
Airlock	#1210 drop-thru cast iron	#1210 drop-thru cast iron	#1210 drop-thru cast iron
Frame	1 piece formed steel	1 piece formed steel	1 piece formed steel
Motor/Power	30 hp gas kohler(22.4 KW)	10,15 or 20 hp (7.5,11,15 KW)	540 PTO (25 + hp)
Starter	12 volt	"across the line"	not applicable
Receiver	18" dia. x 36" high (46 x 91 cm)	18" dia. x 36" high (46 x 91 cm)	18" dia. x 36" high (46 x 91 cm)
Inlet	4" (100 mm) daffin couplings with plugs	4" (100 mm) daffin couplings with plugs	4" (100 mm) daffin couplings with plugs
Outlet	4" (100 mm) daffin couplings with plugs	4" (100 mm) daffin couplings with plugs	4" (100 mm) daffin couplings with plugs

Due to continuous product development, specifications are subject to change without notice.



BLOWER/AIRLOCK

- 510 positive displacement WALINGA blower
- 12" x 10" (31x26 cm) Drop-Thru Airlock
- Combination belt/chain drive



3510 G

OPTIONS

- Stainless steel hoses
- 3" (75 mm) rubber suction hose
- Discharge cyclone
- Remote shut off (gas model only)



3510 E

ACCESSORIES

- Nozzle:
- 4" Suction Nozzle
- 4" (100 mm) with cleanup head Hoses:
- One 4" x 12' (100 mm x 3.65 m) rubber suction hose
- One 4" x 12' (100 mm x 3.65 m) galvanized discharge hose



3510 3PH

CAPACITIES:

Model	Product	Barley		Corn		Wheat		Beans	
		Bu/hr	Tonnes per hr	Bu/hr	Tonnes per hr	Bu/hr	Tonnes per hr	Bu/hr	Tonnes per hr
3510 G (30 hp)		900	23	700	18	575	15	500	13
3510 E (20 hp)		700	18	650	17	500	13	450	12
3510 E (15 hp)		550	14	500	13	375	10	350	9
3510 E (10 hp)		400	10	350	9	250	7	225	6
3510 3PH		700	18	650	17	500	13	450	12

*Capacities based on using 12' (3.5 m) long suction line and truck loading kit. Capacity will vary with condition of product.



www.walinga.com

Head office:
938 Glengarry Cres.
Fergus ON. Canada
N1M 2W7
Tel (519) 787-8227
Fax (519) 787-8210

Michigan:
1190 Electric Ave.
Wayland, MI.
USA 49348
Tel (800) 466-1197
Fax (616) 877-3474

Manitoba:
70 3rd Ave. N.E. Box 1790
Carman, Manitoba
Canada R0G 0J0
Tel (204) 745-2951
Fax (204) 745-6309

Saskatchewan:
P.O. Box 849
220 Frontage Rd.
Davidson, Saskatchewan
Canada S0G 1A0
Tel (306) 567-3031
Fax (306) 567-3039